

SONALIKA SIKANDER 4WD

RX 42

RX 47

RX 50

SABSE **KAM DIESEL** MEIN

SABSE **ZYADA TAAQAT** AUR **RAFTAAR**

3 Cylinder, Big Powerful High Torque Engine
(Torque 197 - 210 Nm)

Fully Sealed 4WD Super Steer Axle

High lift Capacity with Precision Servo
Control Valve

SONALIKA
LEADING AGRI EVOLUTION

**4WD FULLY SEALED AXLE
FOR HIGH GROUND CLEARANCE**



WORLD'S NO. 1 PLANT MEIN NIRMIT

HEAVY DUTY TRACTOR RANGE

For more information please contact :

TOLL FREE NO. 1800 102 1011

www.sonalika.com

4WD SIKANDER SPECIFICATION

MODELS		DI-42 HDM 4WD	DI-47 HDM 4WD	DI-50 4WD
ENGINE	Capacity, cc	2891	3065	3065
	Torque, Nm	197	205	210
	No. of Cylinders	3	3	3
	Rated ERPM	1800	1900	2000
	Air Cleaner Type	Dry type with Pre-cleaner & clogging sensor		
HYDRAULICS, STEERING, BRAKES & TRANSMISSION	Gear Box Type	Constant Mesh Side Gear		
	Clutch Type	Dual		
	No. of Speeds - Standard	8F+2R		
	Forward Speeds (Min-Max), Km/h	2.69 - 33.45	2.82 - 33.27* 2.96 - 34.92	2.56 - 36.58
	PTO RPM	540@ 1680		
	Brakes Type	Multidisc OIB		
	Front Axle	4 WD Heavy Duty Sealed		
	Steering Type	Independent Power Steering		
	Hyd. Lift capacity, Kg	2200		
	Hydraulic Control Valve	1 DA (Double Acting) Hydraulic Auxiliary Valve		
WEIGHT & DIMENSIONS	Front Tyre	203.2mm - 457.2mm (8.0-18)	203.2mm - 457.2mm (8.0-18)* 210.82mm - 508mm (8.3-20)	210.82mm - 508mm (8.3-20)
	Rear Tyre	345.44mm - 711.2mm (13.6-28)	345.44mm - 711.2mm (13.6-28)* 378.46mm - 711.2mm (14.9-28)	378.46mm - 711.2mm (14.9-28)
	Overall Length, mm	3610 - 3630		
	Overall Width, mm	1810 - 1825		
	Wheelbase, mm	2110	2110	2115
	Track width, mm	1250 - 1530		
	Mass (Unballasted), Kg	2200	2200	2260

*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. Please correlate with latest updates, accessories shown may not be part of standard product. E&OE



HDM ENGINE



HS-HT GEAR BOX



1 DA HYDRAULIC
AUXILIARY VALVE



FULLY SEALED 4WD AXEL WITH
HIGH GROUND CLEARANCE
FOR DRY / WET LAND



PRECISE HYD. CONTROL
WITH HIGH LIFT CAPACITY



ERGO STEERING



NEXT GENERATION SEAT



CCS WIDE PLAT FORM



MODERN POWERFUL
STYLING



PUDDLING MASTER

Advantages

- ♦ **Big, Powerful High Torque Engine & 4WD** - Faster Pick-up and More Coverage with best Performance in Tough Conditions

- ♦ **Fully Sealed 4WD Front Axle** - Trouble Free Working
- ♦ **Independent Power Steering** - High Performance Steering enabling quick & easy turning in less space
- ♦ **Higher Ground Clearance** - Easy to overcome obstacles
- ♦ **Optimum Weight** - Ensure high traction and less slippage resulting more coverage.



POTATO MASTER

Advantages

- ♦ **Big & Powerful Engine & 4WD** - Better Pulling and minimum Slippage
- ♦ **2200 Kg Lift Capacity** - Easy Lifting of heavy Implements.
- ♦ **High Precision Hydraulics with Servo Hyd. Valve** - Best Sensing for Uniform depth
- ♦ **DCV with QRC** - Precise Operation & Quick Fitment
- ♦ **Higher Wheel Base and Better Weight Distribution** - Higher Stability with Heavy Implements and haulage
- ♦ **Adjustable Front Axle with 1.25 m to 1.53 m Track Width** - No Disturbance to potato crop
- ♦ **Low Turning Radius** - Quick Turning in less Space without disturbing potato crop

WORLD'S NO. 1 PLANT MEIN NIRMIT
HEAVY DUTY TRACTOR RANGE

International Tractors Limited

Head Office & Plant: Village Chak Gujran, P.O. Piplanwala- 146022 Jalandhar Road, Hoshiarpur (Pb.) - INDIA | Phone: +91-1882-522220, 522221 | Fax: +91-1882-522222

Marketing Office: C-133 A, Sector-2, Noida (UP) - 201301 | Phone: +91-120-4095860

www.sonalika.com | welcome@sonalika.com | https://twitter.com/Sonalika_India | https://www.facebook.com/SonalikaTractorsOfficial | https://www.youtube.com/channel/UCY_A8yslhLO3FUbmtRsRCxQ