

For more information please contact:

TOLL FREE NO. 1800 102 1011

4WD SIKANDER SPECIFICATION

	MODELS	DI-42 HDM 4WD	DI-47 HDM 4WD	DI-50 4WD
ENGINE	Capacity, cc	2891	3065	3065
	Torque, Nm	197	205	210
	No. of Cylinders	3	3	3
	Rated ERPM	1800	1900	2000
	Air Cleaner Type	Dry type with Pre-cleaner & clogging sensor		
HYDRAULICS, STEERING, BRAKES & TRANSMISSION	Gear Box Type	Constant Mesh Side Gear		
	Clutch Type	Dual		
	No. of Speeds - Standard	8F+2R		
	Forward Speeds (Min-Max), Km/h	2.69 - 33.45	2.82 - 33.27 2.96 - 34.92	2.56 - 36.58
	PTO RPM	540@ 1680		
	Brakes Type	Multidisc OIB		
	Front Axle	4 WD Heavy Duty Sealed		
	Steering Type	Independent Power Steering		
	Hyd. Lift capacity, Kg	2000		
	Hydraulic Control Valve	1 DA (Double Acting) Hydraulic Auxiliary Valve		
WEIGHT & DIMENSIONS	Front Tyre	203.2mm - 457.2mm (8.0-18)	203.2mm - 457.2mm (8.0-18) 210.82mm - 508mm (8.3-20)	210.82mm - 508mm (8.3-20)
	Rear Tyre	345.44mm - 711.2mm (13.6-28)	345.44mm - 711.2mm (13.6-28) 378.46mm - 711.2mm (14.9-28)	378.46mm - 711.2mm (14.9-28)
	Overall Length, mm	3600 - 3630		
	Overall Width, mm	1810 - 1825		
	Wheelbase, mm	2130		
WE	Track width, mm	1250 - 1530		
	Mass (Unballasted), Kg	2200	2200	2260



PUDDLING MASTER

Advantages

- Big, Powerful High Torque Engine & 4WD - Faster Pick-up and More Coverage with best Performance in **Tough Conditions**
- Fully Sealed 4WD Front Axle Trouble Free Working
- Independent Power Steering High Performance Steering enabling quick & easy turning in less space
- Higher Ground Clearance Easy to overcome obstacles
- Optimum Weight Ensure high traction and less slippage resulting more coverage.

POTATO MASTER


Advantages

- Big & Powerful Engine & 4WD Better Pulling and minimum Slippage
- 2000 Kg Lift Capacity Easy Lifting of heavy Implements.
- High Precision Hydraulics with Servo Hyd. Valve Best Sensing for Uniform depth
- DCV with QRC Precise Operation & Quick Fitment
- Higher Wheel Base and Better Weight Distribution Higher Stability with Heavy Implements and haulage
- Adjustable Front Axle with 1.25 m to 1.53 m Track Width No Disturbance to potato crop
- Low Turning Radius Quick Turning in less Space without disturbing potato crop





HS-HT GEAR BOX















CCS WIDE PLAT FORM

MODERN POWERFUL STYLING

WORLD'S NO.

HEAVY DUTY TRACTOR RANGE

International Tractors Limited

Head Office & Plant: Village Chak Gujran, P.O. Piplanwala- 146022 Jalandhar Road, Hoshiarpur (Pb.) - INDIA | Phone: +91-1882-522220, 522221 | Fax: +91-1882-522222

Marketing Office: C-133 A, Sector-2, Noida (UP) - 201301 | Phone: +91-120-4095860











https://www.youtube.com/channel/UCY_A8yslhLO3FUbmtRsRCxQ