





- Samrat is a self propelled wheel type combine harvester best suitable for harvesting of crops like maize, soyabean, toor dal, dhania, bajra, wheat, paddy, moong, corn, barseem etc.
- Higher power (133 bhp) turbo charge inter cooled engine.
- Stainless steel parts in all grain touching areas.
- Optional 4 wheels drive for better traction in semi-wet & wet fields.

INDUSTRY'S 1ST HARVESTER WITH CED BASED PAINT

Self cleaning radiator fan.











Constant mesh



New stylish





Finance available through all major

WORLD'S NO.
HEAVY DUTY RANGE

## **Technical Specification**

•		•				
ENGINE						
Power ( RPM)	:	133 HP Stag	e IV			
No. of Cylinders	:	6				
Air Cleaner	:	Dry Type				
Cooling System	:	Water cooled	d			
CLUTCH						
Type of Clutch	:	Single, Heav	y Duty Dry C	lutch Type		
Dia (mm)	:	330				
TRANSMISSION						
No. of Gears	:	4 Forward	1 R	everse		
Gear Speed (km/hr)						
Forward		Low	Hig	gh		
1st Gear	:	1.8	2.	9		
2nd Gear	:	4	6.	4		
3rd Gear	:	7.25 11.6		.6		
4th Gear	:	15.9	25	5.5		
Reverse	:	5.3	8.	4		
CUTTER BAR MECHANISM						
for Wheat, Paddy & Others						
Width (mm)	:	4.3				
Cutting Height (mm)	:	65-1275				
No. of Blades	:	58				
No. of Guards	:	29				
Stroke (mm)	:	85				
Reel Speed	:	20–55				
Reel Dia (mm)	:	915				
Feeder Housing	:	Chain Type Feeder				
MAIZE						
Cutter Bar Working Width (mm)	:	3.4m, 3.12m				
No. of Rows	:	5/6/7				
Spacing of Rows (mm)	:	457.2 (18"), 609.6 (24"), 762 (30")				
THRESHING MECHANISM						
Thresher Drum		Wheat (Rasp Bar)	Paddy (Peg Tooth)	(Maize Peg Tooth)		
Width (mm)	:	1250	1250	1250		
Diameter of Thresher Drum (mm)	:	605	605	605		
Speed RPM	:	540-1200				
Speed Adjustment	:	By means of	Mechanical	Variator		



STRAW WALKER			
No. of Straw Walker	:	5	
No. of Steps	:	5	
Length (mm)	:	3770	
Width (mm)	:	235	
CLEANING SIEVES AREA			
Upper Sieve Area (m²)	:	2.42	
Lower Sieve Area (m²)	:	1.77	
CAPACITY			
Grain Tank (Cubic mtr)	:	2.5	
Fuel Tank (ltr.)	:	365	
BATTERY			
No. of Batteries	:	2	
Capacity & Rating of each Battery	:	12V, 100	
TYRE		Size	Ply Rating
Front	:	18.4-30	12pr/14pr
Rear	:	9.00-16	16pr
MAIN DIMENSIONS (Approx.)			
In working			
Length (mm)	:	8370	
Width (mm)	:	4665	
Height (mm)	:	3850	
Ground Clearance (mm)	:	370	
In Transport			
Length (mm)	:	12450	
Width (mm)	:	3035	
Height (mm)	:	3850	
Total Weight (Kg.)		9120 with trail	er (Approx.)



5 speed Gear box



Large grain tank capacity enables long working hours with minimum interruption



Threshing drum for Wheat, paddy & other crops



6 bar reel



Longer feeder with 3 flats



Heavy duty straw walker 1.6 mm thick



Large sieve area for optimum grain cleaning



Grain unloading augur self locks



Bigger blower with flow adjustment



Comfortable cushioned driver seat with adjustable height



Projector type head lighting



Heavy duty rear axle / offset axle



133 hp stage IV Engine



Tool kit - Safety lock



Extra capacity diesel tank

## HEAVY DUTY RANGE

## **INTERNATIONAL CARS & MOTORS LTD.**

**Plant:** 25th Milestone NH70, (Una–Amb Road), Industrial Area, Amb, Distt. Una (HP) 177203 **Tel.:** +91–1976–304314, **Fax:** +91–1976–304315 **Email:** info@sonalikaindustries.com

**Authorised Dealer** 

30042255A