

SONALIKA
LEADING AGRI EVOLUTION

SONALIKA
SIKANDER

DI 42

SABSE **KAM DIESEL** MEIN

SABSE **ZYADA TAAQAT** AUR **RAFTAAR**

KING OF FIELDS

Unmatched Power - Can Operate
0.33m Bigger Rotavator W.R.T.
other brands

Highest Torque - 197 Nm

Fingertip control hydraulics -
Uniform depth - better yield

CHAMPION ON ROADS

Easy lifting of trolley with company
fitted DCV (Trolley Pressure Pipe)

Maximum Speed - Best speed in
category 34.07 km/h

Best Stability - Zero front
end lifting.



WORLD'S NO. 1 PLANT MEIN NIRMIT
HEAVY DUTY TRACTOR RANGE

For more information please contact :
TOLL FREE NO. **1800 102 1011**

www.sonalika.com



SABSE **KAM DIESEL** MEIN

SABSE **ZYADA TAAQAT** AUR **RAFTAAR**

PARAMETERS	SWARAJ 742 FE	MF 241	MM 475 XP+	JD 5042 D PP	DI-42 HDM
Engine Power (cc)	3136	2500	NA	2940	2891
Maximum Torque (Nm)	161	148.8	171.3	132.4	197
Maximum Speed (km/h)	29.47	30.38	29.8	30.92	34.07
Hydraulic Lift Capacity (kg)	1800	1900	1450	1600	2000
Gear Oil Changing Period (Hrs)	1600	600	1200	1250	1800

Note: Above details are as per respective CFMTTI Budni reports / web information from manufacturers, Data for strictly internal usage only.

BETTER THAN OTHERS

Powerful Engine

More power to operate heavy agriculture equipment's and Haulage work

Highest Backup & Maximum Torque

Zero RPM drop on heavy applications - More diesel saving

Best Speed Combinations

Better productivity per hour - More earning

Best Lifting Capacity

Easy to operate with heavy loads

Heavy Duty Parts




More saving due to lowest maintenance cost

DI-42 HDM SIKANDER SPECIFICATION

Model	DI-42 HDM
Drive	2WD
Engine	4 Stroke, Direct Injection, Water Cooled, Diesel Engine
No of Cylinder/ Displacement	3 / 2891cc
H.P. Category	42
Rated Engine Speed	1800
Transmission Type	Constant Mesh
Speed Range km/h	2.46 - 34.07
PTO	540
Clutch Type	Single Clutch / Dual Clutch
Brakes	Dry Disc / OIB
Steering Type	Mechanical / Power
Wheel Base	1970 mm / 2080 mm (with Power Steering)
Lifting Capacity	2000 kg
Front Tyre	152.4mm - 406.4mm (6.0-16)
Rear Tyre	345.44mm - 711.2mm (13.6-28)

Options Available

**MANUFACTURED
IN THE WORLD
NO.1 PLANT**



*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE, Please correlate with latest updates, accessories shown may not be part of standard product.

WORLD'S NO.1 PLANT MEIN NIRMIT

HEAVY DUTY TRACTOR RANGE

International Tractors Limited

Head Office & Plant: Village Chak Gujran, P.O. Piplanwala- 146022 Jalandhar Road, Hoshiarpur (Pb.) - INDIA | **Phone:** +91-1882-522220, 522221 | **Fax:** +91-1882-522222

Marketing Office: C-133 A, Sector-2, Noida (UP) - 201301 | **Phone:** +91-120-4095860

www.sonalika.com | welcome@sonalika.com | https://twitter.com/Sonalika_India | <https://www.facebook.com/SonalikaTractorsOfficial> | https://www.youtube.com/channel/UCY_A8yslhLO3FUbmtRsRCxQ

LES\$D42X21023