

SONALIKA
LEADING AGRI EVOLUTION

SONALIKA
SIKANDER

DI 42



SABSE **KAM DIESEL** MEIN

SABSE **ZYADA TAAQAT** AUR **RAFTAAR**

KING OF FIELDS

CHAMPION ON ROADS

Unmatched Power - Can Operate
0.33m Bigger Rotavator W.R.T.
other brands

Easy lifting of trolley with company
fitted DCV (Trolley Pressure Pipe)

Highest Torque - 197 Nm

Maximum Speed - Best speed in
category 34.07 km/h

Fingertip control hydraulics -
Uniform depth - better yield

Best Stability - Zero front
end lifting.



WORLD'S NO. 1

HEAVY DUTY TRACTOR RANGE

For more information please contact :
TOLL FREE NO. **1800 102 1011**

www.sonalika.com



SABSE **KAM DIESEL** MEIN

SABSE **ZYADA TAAQAT** AUR **RAFTAAR**

PARAMETERS	SWARAJ 843 XM	MF 241 DI MS	M&M 475 DI NKOM BP	JD 5042 D	DI-42 HDM SIKANDER
Engine Power (cc)	2730	2500	2730	2940	2891
Maximum Torque (Nm)	166.7	158.2	159.8	144.9	197
Maximum Speed (km/h)	29.3	29.3	28.34	30.88	34.07
Hydraulic Lift Capacity (kg)	1200	1700	1500	1600	2000
Gear Oil Changing Period (Hrs)	1600	600	1200	1250	1800

Powerful Engine

More power to operate heavy agriculture equipment's and Haulage work

Highest Backup & Maximum Torque

Zero RPM drop on heavy applications - More diesel saving

Best Speed Combinations

Better productivity per hour - More earning

Best Lifting Capacity

Easy to operate with heavy loads

Heavy Duty Parts

More saving due to lowest maintenance cost

DI-42 HDM SIKANDER SPECIFICATION

Model	DI-42 HDM
Drive	2WD
Engine	4 Stroke, Direct Injection, Water Cooled, Diesel Engine
No of Cylinder/ Displacement	3 / 2891cc
H.P. Category	42
Rated Engine Speed	1800
Transmission Type	Constant Mesh
Speed Range km/h	2.46 - 34.07
PTO	540
Clutch Type	Single Clutch / Dual Clutch
Brakes	Dry Disc / OIB
Steering Type	Mechanical / Power
Wheel Base	1970 mm / 2080 mm (with Power Steering)
Lifting Capacity	2000 kg
Front Tyre	152.4mm - 406.4mm (6.0-16)
Rear Tyre	345.44mm - 711.2mm (13.6-28)

Options Available

Note: Above details are as per respective CFMTTI Budni reports / web information from manufacturers. Data for strictly internal usage only.

**MANUFACTURED
IN THE WORLD
NO.1 PLANT**



*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE. Please correlate with latest updates, accessories shown may not be part of standard product.

WORLD'S NO. 1

HEAVY DUTY TRACTOR RANGE

International Tractors Limited

Head Office & Plant: Village Chak Gujran, P.O. Piplanwala- 146022 Jalandhar Road, Hoshiarpur (Pb.) - INDIA | Phone: +91-1882-522220, 522221 | Fax: +91-1882-522222

Marketing Office: C-133 A, Sector-2, Noida (UP) - 201301 | Phone: +91-120-4095860

www.sonalika.com | welcome@sonalika.com | https://twitter.com/Sonalika_India | https://www.facebook.com/SonalikaTractorsOfficial | https://www.youtube.com/channel/UCY_A8ysiHL03FUbmRRCxQ

LESSD42X20421