

SONALIKA

जीतजे का
GH

DI 740 III HDM



HEAVY DUTY TRACTOR

Taqat ka Bejod Baadshah

King of Fields

Unmatched Power:
Can operate 0.33 M
Bigger Rotavator (in category)

Maximum Torque:
(197 Nm)

Best Turning Radius
in its category (3.24 M)

Champion on Roads

Maximum Speed:
Best in category: 34.07 km/h

Easy lifting of trolley with company
fitted DCV (Trolley Pressure Pipe)

Optimum Balance : Zero front end
lifting.



For more information please contact :

TOLL FREE NO. 1800 102 1011

www.sonalika.com

DI 740 III HDM HEAVY DUTY TRACTOR

DI 740 III HDM - Taqat ka Bejod Baadshah

POWERFUL ENGINE (2891 cc DISPLACEMENT)

Best power availability for farming & haulage.

MAXIMUM TORQUE (197 Nm)

Negligible RPM drop even on sudden heavy load- Best in diesel saving.

KING OF ROTAVATOR

Best coverage by 0.33 M bigger Rotavator.

UNMATCHED SPEED (34.07 km/h)

Per hour best coverage in field and more haulage trips.

HEAVY DUTY PARTS

Heavy Duty design of parts for longer life & best return on investment.

BALANCED & COMPLETE

No tyre slippage and front end lifting.

ZA POWER SONALIKA Hallmark of HEAVY DUTY

Zero acceleration power test proves that Sonalika is more powerful than other tractors.

It can pull cultivator, immersed in soil along with the load of 3-4 persons on minimum RPM (600-700) & L1 gear combination.

This unmatched performance is due to optimum design combination of Heavy Duty Backup Torque, Heavy Duty Parts, Powerful Engine & Heavy Duty Gear Box.

“Truly, a HEAVY DUTY Tractor !”

Product improvement is a continue process at ITL,
above specification may change without pre-information.

Contact nearest dealer for latest updates.

Accessories shown are not part of standard product.

*Product performance claims are under standard conditions.

LEQD740IIIHDMX10126

DI 740 HDM Technical Specification

Model	DI-740 HDM
Drive	2WD
Engine	4 Stroke, Direct Injection, Water Cooled, Diesel Engine
No of Cylinder/ Displacement	3/2891 cc
H.P. Category	42
Rated Engine Speed	2000
Transmission Type	Constant Mesh
Speed Range km/h	2.46 to 34.07
PTO	540
Clutch Type	Single Clutch/Dual Clutch
Brakes	OIB
Steering Type	Mechanical / Power
Wheel Base	1970 mm / 2080 mm (with Power Steering)
Lifting Capacity	2000 kg
Front Tyre	152.4mm - 406.4mm (6.0-16)
Rear Tyre	345.44mm - 711.2mm (13.6-28)

OIB



Less Maintenance, Longer Life

COOLANT RECOVERY BOTTLE



Zero coolant wastage & best cooling operation

TIPPING TRAILER CONNECTION



Easy to operate Trolley

HEAVY DUTY BUMPER



Tractor never lifts from the front

INTERNATIONAL TRACTORS LIMITED

C-133A, Sector-2, Noida- 201301 (U.P.)

Ph. : +91 120 4095860

Fax : +91 11 22377472, 22370492

TOLL FREE NO. 1800 102 1011

Website : www.sonalika.com