

SONALIKA
LEADING AGRI EVOLUTION

SONALIKA
SIKANDER

DI 745 III



SABSE **KAM DIESEL** MEIN

SABSE **ZYADA TAAQAT** AUR **RAFTAAR**

KING OF FIELDS

CHAMPION ON ROADS

Unmatched Power - Can Operate
0.33m Bigger Rotavator W.R.T.
other brands

Easy lifting of trolley with company
fitted DCV (Trolley Pressure Pipe)

Highest Torque - 205 Nm

Maximum Speed - Best speed in
category 34.92 km/h

Fingertip control hydraulics -
Uniform depth - better yield

Best Stability - Zero front
end lifting.



WORLD'S NO. 1

HEAVY DUTY TRACTOR RANGE

For more information please contact :
TOLL FREE NO. 1800 102 1011

www.sonalika.com

PARAMETERS	M&M 575 DI MKM BP	FT 45	SWJ 744 FE XT	MF 245	DI-745 III HDM
Engine Power (cc)	2730	3140	3307	2700	3065
Maximum Torque (Nm)	166.3	186.5	192	158.2	205
Maximum Speed (km/h)	29.34	29.29	29.23	33.15	34.92
Hydraulic Lift Capacity (kg)	1600	1500	1500	1700	2000
Gear Oil Changing Period (Hrs)	1200	1200	1600	750	1800

Note: Above details are as per respective CFMTTI Budni reports / web information from manufacturers. Data for strictly internal usage only.

BETTER THAN OTHERS

Powerful Engine
More power to operate heavy agriculture equipment's and Haulage work

Highest Backup & Maximum Torque
Zero RPM drop on heavy applications - More diesel saving

Best Speed Combinations
Better productivity per hour - More earning

Best Lifting Capacity
Easy to operate with heavy loads

Heavy Duty Parts
More saving due to lowest maintenance cost

DI-745 III HDM SIKANDER SPECIFICATION

Model	DI-745 III HDM
Drive	2WD
Engine	4 Stroke, Direct Injection, Water Cooled, Diesel Engine
No of Cylinder/ Displacement	3 / 3065 cc
H.P. Category	50
Rated Engine Speed	1900
Transmission Type	Constant Mesh
Speed Range km/h	2.55 - 33.27 / 2.67 - 34.92 #
PTO	540
Clutch Type	Single Clutch / Dual Clutch
Brakes	Dry Disc / OIB*
Steering Type	Mechanical / Power
Wheel Base	2080 mm
Lifting Capacity	2000 kg
Front Tyre	152.4mm - 406.4mm (6.0-16) / 165.1mm - 406.4mm (6.5-16) / 190.5mm - 406.4mm (7.5-16)
Rear Tyre	345.44mm - 711.2mm (13.6-28) / 378.43mm - 711.2mm (14.9-28)

Options Available: DI-745 III HDM S1-*, DI-745 III HDM S2-#, DI-745 III HDM S3-**

MANUFACTURED IN THE WORLD NO.1 PLANT



*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE. Please correlate with latest updates, accessories shown may not be part of standard product.

WORLD'S NO. 1

HEAVY DUTY TRACTOR RANGE

International Tractors Limited

Head Office & Plant: Village Chak Gujran, P.O. Piplanwala- 146022 Jalandhar Road, Hoshiarpur (Pb.) - INDIA | Phone: +91-1882-522220, 522221 | Fax: +91-1882-522222

Marketing Office: C-133 A, Sector-2, Noida (UP) - 201301 | Phone: +91-120-4095860

www.sonalika.com | welcome@sonalika.com | https://twitter.com/Sonalika_India | https://www.facebook.com/SonalikaTractorsOfficial | https://www.youtube.com/channel/UCY_A8ysihL03FUbmRRCxQ