

SALIENT FEATURES

- Suitable for light & medium soil.
- High quality boron steel disc.
- Tillage depth of harrow 127–178 mm.
- Used for chop-up unwanted weeds or crop residues.
- Useful for open field for superficial ploughing for shattering of clods, preparing seed bed, burial of organic substance & remains of cut of crop.
- Maintenance free performance & longer life.
- Better pulverization.
- It can be easily mounted & attached with any tractor model.
- Used for breaking down soil clods into smaller pieces.






Heavy duty SG Iron bearing hub



Combination of notched & plain boron steel discs



Adjustment rod



Gang axle lock

			<i>TECHNICA</i>	L DATA			
DESCRIPTION		6x6	7x7	8X8	9x9	10x10	12x12
Frame (mm)	75x10 Angle Frame with 100 x 50 Front Channel						
Gang Bolt / Axle (mm)	31.5 (Solid Sq. Rod)						
No. of Disc	933	12	14	16	18	20	24
Type of Disc		Notched Disc in Front Gang & Plain Disc in Rear Gang					
Disc Diameter (mm)		560					
Disc Spacing (mm)	41	228					
Bearing Hubs		4		6	8		
Mounted Cat.		CAT-II					
Width of Cut (mm)	I+I	1370-1420	1585-1635	1798-1852	2018-2068	2235-2285	2668-2718
Weight (kg) Approx ±5%	010	390	430	500	575	615	730
Tractor Power (HP)	00	30+	40+	50+	60+	75+	90+

*The Product & Specifications are subject to change / discontinue without any notice on the sole discretion of manufacturer.

WORLD'S NO.
HEAVY DUTY RANGE

SONALIKA INDUSTRIES

(A UNIT OF INTERNATIONAL CARS & MOTORS LTD.)

Works & Admin Office: Vill. Chak Gujran, Jalandhar Road, Hoshiarpur -146 022 (Pb.), India

Tel.: +91 9914934 522, +91 1882-501300, Email: info@sonalikaindustries.com

Authorised Dealer