

For more information please contact:

HEAVY DUTY TRACTOR RANGE

SPECIFICATION

TRACTOR MODEL	SONALIKA GARDENTRAC
ENGINE	
Engine Description	Mitsubishi MVL3E
HP Category	20
Туре	4 Stroke Water Cooled
No. of Cylinder	3
Bore/Stroke	76 / 70 mm
Displacement	952 cc
Rated Engine Speed (RPM)	2700
Maximum Torque (NM)	52@2000 RPM
Silencer	Horizontal
Air Cleaner	Oil Bath with Pre-Cleaner
MEASUREMENT	
Wheel Base	1420 mm
Total Length	2560 mm
Total Width	970 mm
Total Height	1230 mm
Ground Clearance	200 mm
Standard Front Track Width	775 mm
Standard Rear Track Width	720 mm
Weight	790 kg
CLUTCH	
Clutch Type	Single Clutch / 180 mm
BRAKE	Mechanical, Expended Shoe Type

TRANSMISSION	
Туре	Sliding Mesh, 6 Forward, 2 Reverse
SPEED KM/H	
Forward	1.27 to 14.19
Reverse	1.63 to 7.16
РТО	
PTO RPM	575, 848 & 1465 @ 2700 Rated RPM
TURNING RADIUS (mm)	
With Brake	2.11 M
Without Brake	2.35 M
HYDRAULIC	
Lifting Capacity	650 kg
TYRE	
Front	127mm - 304.8mm (5-12)
Rear	203.2mm - 457.2mm (8-18)
CAPACITY	
Fuel Tank Capacity	High Speed Diesel 31.5 Ltr.
Engine Oil	3.6 Ltr.
Hydraulic + Transmission	17 Ltr.
ELECTRICAL PARTS	
Battery	12 V, 50 Ah
Uses	Rotavator, Cultivator, Spraying Ploughing, Transportation, Puddling etc

Multi Utility Tractor

SONALIKA GARDENTRAC DI-20



Most Suitable for all Types of Crops (Groundnuts, Pomegranate, Sugarcane, Cotton, Grapes etc.)







Best in Rotavator, Spraying, Ploughing, Cultivator, Harrow Transportation & Puddling Applications

Authorised Dealer

INTERNATIONAL TRACTORS LIMITED

C-133A, Sector-2, Noida- 201301 (U.P.)

Ph.: +91 120 4095860 Fax: +91 11 22377472, 22370492 TOLL FREE NO. 1800 102 1011 Website: www.sonalika.com

*Product performance claims are under standard conditions.

Product improvement is a continue process at ITL, above specification may change without pre-information. **Contact nearest dealer for latest updates.** Accessories shown are not part of standard product.