

INDIA'S 1st PUDDLING SPECIAL TRACTOR

SONALIKA
మహాబలి
PADDY SPECIAL
RX42P+

SONALIKA

जीतने का
दम



MAHA

TORQUE + RAFTAR + COMFORT



MAHA TORQUE
Fastest Pick Up



MAHA RAFTAR
15 Gears for high performance
agriculture & field operations



Shuttle Reverser

MAHA COMFORT
Single Lever
Forward - Reverse Puddling



10+5
Fastest Working

Special 5 Gear

For more information please contact :

TOLL FREE NO. **1800 102 1011**

www.sonalika.com

TECHNICAL SPECIFICATIONS

MODEL	DI-42 Power Plus
ENGINE	
Capacity, cc	2893
No. of cylinder	3
HP Category	45
Max. Torque, Nm	185.4
TRANSMISSION	
Max. PTO HP	40.93
No of Gears	10F+5R
Trans. Type	CM
Position of Gear	Side Shift
Final Reduction	Bull Gear & Pinion
HYDRAULIC	
Clutch Type	Dual / Double
Lift capacity, kg	2000
Hydr. (High Precision)	Live ADDC
TYRES	
Rear Tyre size	345.44mm - 711.2mm (13.6-28) 378.46mm - 711.2mm (14.9-28)*

FULL CAGE WHEEL PUDDLING

- ▶ 185.4 Nm - Higher Max Torque ensures fastest pick up & Lowest motion drop
- ▶ 5F+3R - More optimized speed for fast puddling & more coverage
- ▶ Shuttle Reverser - Quick & easy Forward & Reverse with single lever



HALF CAGE WHEEL PUDDLING

- ▶ 185.4 Nm - Higher Max Torque ensures fastest pick up & Lowest motion drop
- ▶ 5F+3R - More optimized speeds for fast puddling & more coverage
- ▶ 390 mm - High ground clearance to easily cross bunds from one field to another



ROTAVATOR

- ▶ 40.93 HP - Max. PTO power to drive Bigger Rotavator
- ▶ Adv. 5G Hyd. Sensing - With 2000 kg Lift capacity for precision setting & uniform operations
- ▶ 185.4 Nm - Max Torque ensures better pulverization of soil



LESMR42X10126

BEST IN CLASS

MODEL	DI-42 P+ 🏆	JD 5045 D	MM 575 XP+
Max. Speed (km/h)	37.50	30.92	29.73
Max. Torque (Nm)	185.4	146	180.1
Max. PTO (HP)	40.93	38.2	40.23
No of Gears	10F+5R	8F+4R	8F+2R
Lift capacity (kg)	2000	1600	1600

*Options Available

Note: Above details are as per respective CFMTTI Bodhi reports / web information from manufacturers, Data for strictly internal usage only.

MAHA FEATURES



BIGGER RADIATOR WITH OVERFLOW RESERVOIR - Long working hours without hassle



10F+5R SHUTTLE TECH - 15 Gears for high performance agriculture & field operations



5G HYDRAULICS Smart Sensing with 140+ settings



HEAT PROTECTOR SHIELD - Protection from Engine Heat

*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE, Please correlate with latest updates, accessories shown may not be part of standard product.

International Tractors Limited

Head Office & Plant: Village Chak Gujran, P.O. Piplanwala- 146022, Jalandhar Road, Hoshiarpur (Pb.) - INDIA | Phone: +91-1882-522220, 522221 | Fax: +91-1882-522222

Marketing Office: C-133 A, Sector-2, Noida (UP) - 201301 | Phone: +91-120-4095860

🌐 www.sonalika.com | 🐦 https://twitter.com/Sonalika_India | 📘 <https://www.facebook.com/SonalikaTractorsOfficial> | 📺 <http://www.youtube.com/sonalikatractorsindia>