

INDIA'S 1st PUDDLING SPECIAL TRACTOR



SONALIKA
మహబలి
PADDY SPECIAL
RX 42 P+ 4WD

SONALIKA
జీతనే కా
GH



Available with iPTO
Rotary tools are easy to use



Special 5 Gear



For more information please contact :

TOLL FREE NO. 1800 102 1011

www.sonalika.com

TECHNICAL SPECIFICATIONS

MODEL	DI 42 POWER PLUS 4WD
ENGINE	
Capacity (cc)	2893
No. of cylinder	3
Max. Torque (Nm)	185.4
TRANSMISSION	
Max. PTO (HP)	40.93
No of Gears	10F+5R
Trans. Type	Constant Mesh
Position of Gear	Side Shift
Final Reduction	Bull Gear & Pinion
Max Speed (km/h)	37.50
HYDRAULIC	
Clutch Type	Dual / Double* Clutch
Lift capacity (kg)	2200
Hydr. (High Precision)	Live ADDC with Exso Sensing Hydraulics
TYRES	
Rear Tyre size	345.44mm - 711.2mm (13.6-28) 378.46mm - 711.2mm (14.9-28)*

FULL CAGE WHEEL PUDDLING

- 185.4 Nm - Higher Max Torque ensures fastest pick up & Lowest motion drop
- 5F+3R - More optimized speed for fast puddling & more coverage
- Shuttle Reverser - Quick & easy Forward & Reverse with single lever



HALF CAGE WHEEL PUDDLING

- 185.4 Nm - Higher Max Torque ensures fastest pick up & Lowest motion drop
- 5F+3R - More optimized speeds for fast puddling & more coverage
- 270 mm - High ground clearance to easily cross bunds from one field to another



ROTOVATOR

- 40.93 HP - Max. PTO power to drive Bigger Rotovator
- Exso Sensing Hyd. - With 2200 kg Lift capacity for precision setting & uniform operations
- 185.4 Nm - Max Torque ensures better pulverization of soil



BEST IN CLASS

PARAMETERS/ MODELS	DI 42 RX PP 4WD	JD 5045 D 4WD
Max. Speed (km/h)	37.50	30.92
Max. Torque (Nm)	185.4	146
Max. PTO	40.93	38.2
No of Gears	10F+5R	8F+4R
Lift capacity (kg)	2200	1600

MAHA FEATURES



BIGGER RADIATOR WITH OVERFLOW RESERVOIR - Long working hours without hassle



10F+5R SHUTTLE TECH - 15 Gears for high performance agriculture & field operations



ExSo SENSING HYDRAULICS Finger Touch Control



HEAT PROTECTOR SHIELD - Protection from Engine Heat

*Options Available

Note: Above details are as per respective CFMTI Budni reports / web information from manufacturers, Data for strictly internal usage only.

*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE, Please correlate with latest updates, accessories shown may not be part of standard product.

International Tractors Limited

Head Office & Plant: Village Chak Gujran, P.O. Piplanwala- 146022, Jalandhar Road, Hoshiarpur (Pb.) - INDIA | Phone: +91-1882-522220, 522221 | Fax: +91-1882-522222

Marketing Office: C-133 A, Sector-2, Noida (UP) - 201301 | Phone: +91-120-4095860

www.sonalika.com | https://twitter.com/Sonalika_India | <https://www.facebook.com/SonalikaTractorsOfficial> | <http://www.youtube.com/sonalikatractorsindia>