

## **INDIA'S 1**<sup>st</sup> **PUDDLING** SPECIAL TRACTOR





**HEAVY DUTY TRACTOR RANGE** 

For more information please contact : TOLL FREE NO. 1800 102 1011

www.sonalika.com

#### **TECHNICAL SPECIFICATIONS**

MODEL	DI 47 RX 4WD	
ENGINE		
Capacity (cc)	2893	
No. of cylinder	3	
Max. Torque (Nm)	185.4	
TRANSMISSION		
Max. PTO (HP)	40.93	
No of Gears	10F+5R	
Trans. Type	Constant Mesh	
Position of Gear	Side Shift	
Final Reduction	Bull Gear & Pinion	
Max Speed (km/h)	37.5	
HYDRAULIC		
Clutch Type	Dual Clutch	
Lift capacity (kg)	2200	
Hydr. (High Precision)	Live ADDC with Exso Sensing Hydraulics	
TYRES		
Rear Tyre size	378.46mm - 711.2mm (14.9-28)	

### ROTAVATOR + HALF CAGE WHEEL PUDDLING

Higher Max Torque ensures fastest pick up & Lowest RPM drop.

185.4 Nm Torque vs 160.7 Nm Torque for JD 5050 D.

 Optimized speed for best pulverization & more coverage.
 Deter speed for best pulverization of soil

Better speed for best pulverization of soil.

Better fuel saver engine with Exso Sensing Hydraulic with 2200 kg Lift capacity. Exso Sensing Hyd. enables precision setting, Uniform operation with More load handling capacity.



# Higher Max Torque ensures fastest pick up & Lowest RPM drop in toughest conditions. 185.4 Nm Torque vs 160.7 Nm Torque for JD 5050 D. Higher Max speed at rated RPM & Power steering ensures More trips with comfortable ride. 37.50 km/h road speed vs 32.50 km/h for JD 5050 D. Longer over all lengh of the tractor ensures No front lift & more stable in Heavy Haulage application with 2200 kg Lift capacity. 3420 mm vs 3355 mm for JD 5050 D.



### CULTIVATOR

- Higher Max Torque ensures fastest pick up & Lowest motion drop in toughest conditions.
   185.4 Nm Torque vs 160.7 Nm Torque for JD 5050 D.
- Better fuel saver engine with Exso Sensing Hydraulic with 2200 kg Lift capacity. Enable precision setting, Uniform operation with More load handling capacity.
- Better Speed option. 10F + 5R speed option Vs 8F + 4R of JD 5050 D.



### **BEST IN CLASS**

PARAMETERS/ Models	DI 47 RX 4WD 🌥	JD 5050 D 4WD
Max. Speed (km/h)	37.5	32.50
Max. Torque (Nm)	185.4	160.7
No of Gears	10F+5R	8F+4R
Lift capacity (kg)	2200	1600

\*Options Available Note: Above details are as per respective CFMTTI Budni reports / web information from manufacturers, Data for strictly internal usage only.





without basels



10F+5R SHUTTLE TECH -15 Gears for high performance agriculture & field operations



ExSo SENSING HYDRAULICS

HEAT PROTECTOR SHIELD -Protection from Engine Heat ESMR47Y10923

\*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE, Please correlate with latest updates, accessories shown may not be part of standard product.

WORLD'S NO. PLANT MEIN NIRMIT

HEAVY DUTY TRACTOR RANGE

### **International Tractors Limited**

Head Office & Plant: Village Chak Gujran, P.O. Piplanwala- 146022, Jalandhar Road, Hoshiarpur (Pb.) - INDIA | Phone: +91-1882-522220, 522221 | Fax: +91-1882-522222 Marketing Office: C-133 A, Sector-2, Noida (UP) - 201301 | Phone: +91-120-4095860

😌 www.sonalika.com 🛛 🔾 https://twitter.com/Sonalika\_India 🛛 🖪 https://www.facebook.com/SonalikaTractorsOfficial 🗎 🛅 http://www.youtube.com/sonalikatractorsindia