

**SONALIKA**  
LEADING AGRI EVOLUTION

SONALIKA  
**SIKANDER** **RX 47**



SABSE **KAM DIESEL** MEIN

SABSE **ZYADA TAAQAT** AUR **RAFTAAR**

**KING OF FIELDS**

**CHAMPION ON ROADS**

Unmatched Power - Can Operate  
0.33m Bigger Rotavator W.R.T.  
other brands

Easy lifting of trolley with company  
fitted DCV (Trolley Pressure Pipe)

Highest Torque - 205 Nm

Maximum Speed - Best speed in  
category 34.92 km/h

Fingertip control hydraulics -  
Uniform depth - better yield

Best Stability - Zero front  
end lifting.



**WORLD'S NO. 1**

**HEAVY DUTY TRACTOR RANGE**

For more information please contact :

**TOLL FREE NO. 1800 102 1011**

[www.sonalika.com](http://www.sonalika.com)



SABSE **KAM DIESEL** MEIN

SABSE **ZYADA TAAQAT** AUR **RAFTAAR**

PARAMETERS	M&M 575 DI MKM BP	JD 5045 D	SWARAJ 744 FE XT	NH 4710	RX-47 HDM SIKANDER
Engine Power (cc)	2730	2940	3307	2700	<b>3065</b>
Maximum Torque (Nm)	166.3	136.7	192	167.9	<b>205</b>
Maximum Speed (km/h)	29.34	30.54	29.23	31	<b>34.92</b>
Hydraulic Lift Capacity (kg)	1600	1600	1500	1500	<b>2000</b>
Gear Oil Changing Period (Hrs)	1200	1250	1600	1200	<b>1800</b>

### BETTER THAN OTHERS

#### Powerful Engine

More power to operate heavy agriculture equipment's and Haulage work

#### Highest Backup & Maximum Torque

Zero RPM drop on heavy applications - More diesel saving

#### Best Speed Combinations

Better productivity per hour - More earning

#### Best Lifting Capacity

Easy to operate with heavy loads

#### Heavy Duty Parts

More saving due to lowest maintenance cost

Note: Above details are as per respective CFMTTI Budni reports / web information from manufacturers. Data for strictly internal usage only.

### DI-47 RX HDM SIKANDER SPECIFICATION

Model	DI-47 HDM
Drive	2WD
Engine	4 Stroke, Direct Injection, Water Cooled, Diesel Engine
No of Cylinder/ Displacement	3 / 3065 cc
H.P. Category	50
Rated Engine Speed	1900
Transmission Type	Constant Mesh
Speed Range km/h	2.55 - 33.27 / 2.67 - 34.92 *
PTO	540
Clutch Type	Single Clutch* / Dual Clutch / Double Clutch*
Brakes	OIB / Dry Disc*
Steering Type	Power / Mechanical*
Wheel Base	2080 mm
Lifting Capacity	2000 kg
Front Tyre	152.4mm - 406.4mm (6.0-16) / 190.5mm - 406.4mm (7.50-16)
Rear Tyre	345.44mm - 711.2mm (13.6-28) / 378.46mm - 711.2mm (14.9-28)

Options Available:

## MANUFACTURED IN THE WORLD NO.1 PLANT



\*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE. Please correlate with latest updates, accessories shown may not be part of standard product.

WORLD'S NO. 1

HEAVY DUTY TRACTOR RANGE

## International Tractors Limited

Head Office & Plant: Village Chak Gujran, P.O. Piplanwala- 146022 Jalandhar Road, Hoshiarpur (Pb.) - INDIA | Phone: +91-1882-522220, 522221 | Fax: +91-1882-522222

Marketing Office: C-133 A, Sector-2, Noida (UP) - 201301 | Phone: +91-120-4095860

www.sonalika.com | welcome@sonalika.com | https://twitter.com/Sonalika\_India | https://www.facebook.com/SonalikaTractorsOfficial | https://www.youtube.com/channel/UCY\_A8ysiHLO3FUbmRRCxQ