





SABSE ZYADA TAAQAT AUR RAFTAAR

KING OF FIELDS

CHAMPION ON ROADS

Unmatched Power - Can Operate 0.33m Bigger Rotavator W.R.T. other brands

Easy lifting of trolley with company fitted **DCV** (Trolley Pressure Pipe)

Highest Torque - 205 Nm

Maximum Speed - Best speed in category 37.80 km/h

Fingertip control hydraulics – Uniform depth – better yield **Best Stability -** Zero front end lifting.



OF THE RESERVE OF THE PERSON O

WORLD'S NO.

HEAVY DUTY TRACTOR RANGE

SONALIKA



SABSE KAM DIESEL MEIN

SABSE ZYADA TAAQAT AUR RAFTAAR

| PARAMETERS | M&M 575 DI MKM BP | JD 5045 D | SWARAJ 744 FE XT | NH 4710 | RX-47 HDM | SIKALI |
|--------------------------------------|----------------------|--------------|------------------------|------------|-----------|--------|
| Engine Power (cc) | 2730 | 2940 | 3307 | 2700 | 3065 | |
| Maximum Torque (Nm) | 166.3 | 136.7 | 192 | 167.9 | 205 | |
| Maximum Speed (km/h) | 29.34 | 30.54 | 29.23 | 31 | 37.80 | |
| Hydraulic Lift Capacity (kg) | 1600 | 1600 | 1500 | 1500 | 1800 | |
| Gear Oil Changing Period (Hrs) | 1200 | 1250 | 1600 | 1200 | 1800 | |

Powerful Engine

BETTER THAN OTHERS

More power to operate heavy agriculture equipment's and Haulage work

Highest Backup & Maximum Torque

Zero RPM drop on heavy applications -More diesel saving

Best Speed Combinations

Better productivity per hour - More earning

Best Lifting Capacity

Easy to operate with heavy loads

Heavy Duty Parts

More saving due to lowest maintenance cost

DI-47 RX HDM SIKANDER SPECIFICATION

| Model | DI-47 HDM | |
|---------------------------------|--|--|
| Drive | 2WD | |
| Engine | 4 Stroke, Direct Injection, Water Cooled, Diesel Engine | |
| No of Cylinder/ Displacement | 3/3065cc | |
| H.P. Category | 50 | |
| Rated Engine Speed | 1900 | |
| Transmission Type | Constant Mesh | |
| Speed Range km/h | 2.67 - 37.80 / 2.47 - 34.89 # | |
| РТО | 540 | |
| Clutch Type | Single Clutch* / Dual Clutch / Double Clutch* | |
| Brakes | OIB / Dry Disc* | |
| Steering Type | Power / Mechanical * | |
| Wheel Base | 2080 mm | |
| Lifting Capacity | 1800 kg | |
| Front Tyre | 152.4mm - 406.4mm / 190.5mm - 406.4mm (6.0-16 / 7.50-16) | |
| Rear Tyre | 345.44mm - 711.2mm / 378.46mm - 711.2mm (13.6-28 / 14.9-28 | |

Options Available: DI-47 RX HDM S1-*, DI-47 RX HDM S2-#, DI-47 RX HDM S3-*#

MANUFACTURED IN THE WORLD

NO.1 PLANT

manufacturers, Data for strictly internal usage only.





























*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE, Please correlate with latest updates, accessories shown may not be part of standard product

HEAVY DUTY TRACTOR RANGE

WORLD'S NO.

International Tractors Limited

Note: Above details are as per respective CFMTTI Budni reports / web information from

Head Office & Plant: Village Chak Gujran, P.O. Piplanwala- 146022 Jalandhar Road, Hoshiarpur (Pb.) - INDIA | Phone: +91-1882-522220, 522221 | Fax: +91-1882-522222

Marketing Office: C-133 A. Sector-2. Noida (UP) - 201301 | Phone: +91-120-4095860











