

SONALIKA





SABSE KAM DIESEL MEIN

SABSE ZYADA TAAQAT AUR RAFTAAR

### KING OF FIELDS

# **CHAMPION ON ROADS**

**Unmatched Power -** Can Operate **0.33m** Bigger Rotavator W.R.T. other brands

**Easy lifting** of trolley with company fitted **DCV** (Trolley Pressure Pipe)

Highest Torque - 210 Nm

Maximum Speed - Best speed in category 34.47 km/h

**Best Stability -** Zero front end lifting.

Fingertip control hydraulics – Uniform depth – better yield

**HEAVY DUTY TRACTOR RANGE** 





## SABSE KAM DIESEL MEIN

## SABSE ZYADA TAAQAT AUR RAFTAAR

PARAMETERS	EURO 50	JD 5050D	MM 585 XP+	RX-50	SIKANDER	BETTER THAN OTHERS
Engine Power (cc)	2791	2940	2979	3065		Powerful Engine
					ľ	More power to operate heavy agriculture equipment's and Haulage work
Maximum Torque (Nm)	195.3	160.7	198	210	Higi	hest Backup & Maximum Tor
					7 - 3	Zero RPM drop on heavy applications - More diesel saving
Maximum Speed (km/h)	29.30	32.50	30	34.47		Best Speed Combinations
					P.C	etter productivity per hour - More earning
						File productivity per flour - More earning
Hydraulic Lift Capacity (kg)	NA	1600	1850	2000		Best Lifting Capacity
						Easy to operate with heavy loads
Gear Oil Changing Period (Hrs)	600	1250	NA	1800		Heavy Duty Parts
					Mor	e saving due to lowest maintenance cos

## **Powerful Engine**

#### st Backup & Maximum Torque

#### **Sest Speed Combinations**

#### **Best Lifting Capacity**

#### **Heavy Duty Parts**

Note: Above details are as per respective CFMTTI Budni reports / web information from manufacturers, Data for strictly internal usage only.















Model

Drive Engine

PTO

Brakes

Clutch Type

Steering Type

Wheel Base

Front Tyre

Rear Tyre \*Options Available:

Lifting Capacity

No of Cylinder/

Max. Torque. Nm

Rated Engine Speed

Transmission Type

Speed Range km/h

Displacement





MODERN POWERFUL STYLING

**New Attractive Design** 

**DI-50 RX SIKANDER SPECIFICATION** 

4 Stroke, Direct Injection, Water Cooled, Diesel Engine

152.4mm - 406.4mm (6.0-16) / 190.5mm - 406.4\*mm (7.5-16\*)

378.46mm - 711.2mm (14.9-28) / 429.26mm - 711.2\*mm (16.9-28\*)

DI-50 S1 2WD

3 / 3065 cc

Constant Mesh

2.97 - 32.92 / 3.11 - 34.47\*

Single Clutch\* / Dual Clutch

Mechanical\* / Power

210


2000

540

OIB

2010 mm

2000 kg





**WORLD'S NO. PLANT MEIN NIRMIT** 

# **International Tractors Limited**

**HEAVY DUTY TRACTOR RANGE** 

Head Office & Plant: Village Chak Gujran, P.O. Piplanwala- 146022 Jalandhar Road, Hoshiarpur (Pb.) - INDIA | Phone: +91-1882-522220, 522221 | Fax: +91-1882-522222

Marketing Office: C-133 A. Sector-2. Noida (UP) - 201301 | Phone: +91-120-4095860

Better driving in night

E&OE, Please correlate with latest updates, accessories shown may not be part of standard product

\*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice.















LES\$R50X20923