SONALIKA

जीतने का दम

SONALIKA SIKANDER

RX 750 III

SABSE **KAM DIESEL** MEIN

SABSE **ZYADA TAAQAT** AUR **RAFTAAR**

KING OF FIELDS	CHAMPION ON ROADS
Unmatched Power - Can Operate **0.33m** Bigger Rotavator W.R.T. other brands	**Easy lifting** of trolley with company fitted **DCV** (Trolley Pressure Pipe)
Highest Torque - 235 Nm	**Maximum Speed** - Best speed in category **35.49 km/h**
Fingertip control hydraulics – Uniform depth – better yield	**Best Stability** - Zero front end lifting.

TORQUE PLUS

HIGH TORQUE + HIGH SPEED TRANSMISSION

- Higher speed for Best efficiency
- High Torque for Tough Soil conditions
- Fast Pick-up

For more information please contact us:

TOLL FREE NO. **1800 102 1011**

www.sonalika.com

SONALIKA SIKANDER

RX 750 III

SABSE **KAM DIESEL** MEIN

SABSE **ZYADA TAAQAT** AUR **RAFTAAR**

PARAMETERS	ARJUN 555 DI	SWJ 855 FE N	FT 6055	NH 3630 TX	DI-750 III HDM SIKANDER
Engine Power (cc)	3054	3478	3120	2931	3707
Maximum Torque (Nm)	176.3	199.6	179	182.3	235
Maximum Speed (km/h)	30.89	30.9	34.43	31.30	35.49
Hydraulic Lift Capacity (kg)	1800	2000	1509	1795	2200
Gear Oil Changing Period (Hrs)	1200	1200	1200	1200	1800

BETTER THAN OTHERS

Powerful Engine
More power to operate heavy agriculture equipment's and Haulage work

Highest Backup & Maximum Torque
Zero RPM drop on heavy applications - More diesel saving

Best Speed Combinations
Better productivity per hour - More earning

Best Lifting Capacity
Easy to operate with heavy loads

Heavy Duty Parts
More saving due to lowest maintenance cost

Note: Above details are as per respective CFMTTI Budni reports / web information from manufacturers. Data for strictly internal usage only.

RX-750 III POWER PLUS SIKANDER SPECIFICATION

Model	*DI-750 III Rx Power Plus*
Drive	*2WD*
Engine	*4 Stroke, Direct Injection, Water Cooled, Diesel Engine*
No of Cylinder/ Displacement	*4 / 3707 cc*
H.P. Category	*235*
Rated Engine Speed	*1900*
Transmission Type	*8F+2R*
Speed Range km/h	*2.52 - 33.90 / 3.08 - 35.49**
PTO	*540 & Rev*
Clutch Type	*Dual / Double* with IPTO*
Brakes	*OIB*
Steering Type	*Power Steering*
Wheel Base	*2210 mm*
Lifting Capacity	*2200 kg*
Front Tyre	*190.5mm - 406.4mm (7.50-16)*
Rear Tyre	*378.46mm - 711.2mm (14.9-28) / 429.26mm - 711.2mm* (16.9-28*)*

MANUFACTURED IN THE WORLD NO.1 PLANT

LES$R750IIIP+X20126

*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE. Please correlate with latest updates, accessories shown may not be part of standard product.

International Tractors Limited

Head Office & Plant: Village Chak Gujran, P.O. Piplanwala- 146022 Jalandhar Road, Hoshiarpur (Pb.) - INDIA | **Phone:** +91-1882-302220, 302221 | **Fax:** +91-1882-302222

Marketing Office: C-133 A, Sector-2, Noida (UP) - 201301 | Phone: +91-120-4095860

www.sonalika.com | welcome@sonalika.com | https://twitter.com/Sonalika_India | https://www.facebook.com/SonalikaTractorsOfficial | https://www.youtube.com/channel/UCY_A8ysIhLO3FUbmtRsRCxQ