



DESIGNED IN EUROPE

ADVANCED FARMING TECHNOLOGY



Super Luxe DRL



SkySmart® Live Tracking

- Direct Service Connect
- Position Tracking



3x2 Service Promise

Technician within 3 hours
at your door step
Complaint Addressal within 2 Days



Premium Chrome Trims



Twin Barrel Headlamps



Plush Branded Seats
4-Way Adjustment

The Sonalika Tiger series is a first-of-its-kind tractor designed in Europe and made in India to match the needs of young Indian farmers. Built with latest technological features, it is ideal for high-end agricultural applications. Sonalika Tiger series is all set to rule the future of precision farming in India.

Call 1800 102 1011 to book your test drive.



XL W-i-d-e Workspace



Luxurious Multi-function Console



High Stance Seating
180 Degree View



26HP to 60HP

1st Time Features



Intelligent HDM + Engine

- Greater Torque in Every Range
- Extended Service Interval (500 hours)
- Large Cubic Capacity
- More Power in Less Operating RPM
- 4D Air Cooling
- Fuel-Load Balancer



12 + 12 Shuttle Tech Multi Speed

- 12 Specialized Gears for Agricultural Use
- 1 Lever Easy Forward Reverse Operation
- India's Fastest Tractor (39 km/h)



Specifications:

Model	DI - 26 Gardentrac	DI - 47 HDM+ S2	DI - 50 HDM+ S2	DI - 55 HDM+ S2	DI - 60 HDM+ S2
Engine					
Capacity, cc	1318	3065	3065	4087	4087
HP Category	26	50	52	55	60
No. of Cylinders	3	3	3	4	4
Rated E RPM	2700	1900	2000	2000	2100
Max Torque, Nm	81	205	210	230	240
Air Cleaner Type	Dry	Dry	Dry	Dry	Dry
Transmission					
Gearbox Type	Slidingmesh, Side Shift*	Constantmesh, Side Shift	Constantmesh, Side Shift	Constantmesh, Side Shift	Constantmesh, Side Shift
Clutch Type	Single	Dual / Single* / Double*	Dual / Double*	Dual / Double*	Dual / Double*
No. of Speeds -Standard	6F+2R / 12F+4R*	12F + 12R	12F + 12R	12F + 12R	12F + 12R
PTO Type	540 Economy	540 / Rev PTO	540 / Rev PTO	540 / Rev PTO	540 / Rev PTO
Brakes	Multi Disc OIB	Multi Disc OIB	Multi Disc OIB	Multi Disc OIB	Multi Disc OIB
Hydraulics					
Steering Type	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
Lift Capacity, kg	750	2000	2000	2200	2200
Hydraulic Control Valve	1SA	1DA / 1SA*	1DA / 1SA*	1DA / 1SA*	1DA / 1SA*
Tyre					
Tyre Size Front	152.4mm - 304.8mm (6.0-12)	165.1mm - 406.4mm (6.50-16) / 190.5mm - 406.4*mm (7.5-16*) / 152.4mm - 406.4*mm (6.0-16*)	190.5mm - 406.4mm (7.50-16)	190.5mm - 406.4mm (7.5-16) / 165.1mm - 508mm (6.5-20*)	190.5mm - 406.4mm (7.5-16) / 165.1mm - 508mm (6.5-20*)
Tyre Size Rear	210.82mm - 508mm (8.3-20)	378.46mm - 711.2mm (14.9-28)	378.46mm - 711.2mm (14.9-28) / 429.26mm - 711.2*mm (16.9-28*)	429.26mm - 711.2mm (16.9-28)	429.26mm - 711.2mm (16.9-28)

*Optional



Exso-sensing Hydraulics

- 130 Auto-lift Settings
- Independent Hydraulic Pump
- High-lift Capacity (2000-2200 kg)



SkySmart® Live Tracking

- Direct Service Connect
- Position Tracking

International Tractors Limited

Head Office & Plant: Village Chak Gujran, P.O. Piplanwala - 146 022, Jalandhar Road, Hoshiarpur (Punjab) - India
Phone: +91-1882-522220, 522221 | **Fax:** +91-1882-522222,

Marketing office: C-133 A, Sector - 2, Noida - 201 301, Uttar Pradesh, India
Phone: +91-120-4095860 | **Email:** sonalika@sonalika.com | **www.sonalika.com**
Call Center No: 1800 102 1011 (Toll Free)